

Produkt / Nástroj	Rozsah průměrů (mm / inch)												Délkové řady držáků	Použití nástroje					Materiál						Sekce v katalogu		
	3.0-12.7 0-0.5	12.7-25.4 0.5-1.0	25.4-38.1 1.0-1.5	38.1-50.8 1.5-2.0	50.8-63.5 2.0-2.5	63.5-76.2 2.5-3.0	76.2-88.9 3.0-3.5	88.9-101.6 3.5-4.0	101.6-114.3 4.0-4.5	114.3-127.0 4.5-5.0	127.0-139.7 5.0-5.5	139.7-152.4+ 5.5-6.0+		Všeobecné použití	Vysoké posuvy	Hluboké otvory	Velké průměry	Průmyslová specifikace	P	S	M	H	K	N			
ASC 320® 	3.00 - 20.00 (0.1250 - 0.7874)												3.5xD, 6xD, 9xD	●	●	○			●	●	●		●	●	A10		
GEN3SYS® XT Pro 	11.00 - 35.00 (0.4331 - 1.3780)												Extra krátký, 3xD, 5xD, 7xD, 10xD	●	●	●			●				●	●	A20		
GEN3SYS® XT 	11.00 - 35.00 (0.4331 - 1.3780)												Extra krátký, 3xD, 5xD, 5xD, 7xD	●	●				●	●	○	●	●		A20		
GEN2 T-A® 	9.50 - 114.30 (0.3740 - 4.5000)												1xD až 28xD	●	○	●	●		●	●	●		●	●			A30
Original T-A® 	9.50 - 114.30 (0.3740 - 4.5000)												1xD až 28xD	●	○	●	●		●	●	●	○	●	●			A30
High Performance 	24.60 - 127.00 (0.9688 - 5.0000)													●		●	●		●	○	●		○	●		A40	
Universal 	24.60 - 215.90 (0.9688 - 8.5000)													●		●	●		○	○	○		○	○			A40
APX Drill 	33.00 - 101.60 (1.2990 - 4.0000)												3xD, 5xD, 8xD, 10xD	●		●	●		●	○	●		●	●			A50
Revolution Drill® 	47.60 - 101.60 (1.8750 - 4.0000)												1xD, 2.2xD, 2.5xD, 3.5xD, 4.5xD,	○	●		●			●		○	●	●		A60	
Opening Drill® 	50.80 - 142.80 (2.0000 - 5.6200)													○	●		●			●		○	●	●		A70	
Structural Steel: GEN3SYS® XT 	12.00 - 35.00 (0.4724 - 1.3780)												3xD, 5xD, 7xD		○	●		●	●						A91		
Structural Steel: T-A® 	12.98 - 47.80 (0.5110 - 1.8820)												2xD, 4xD, 5xD, 6xD	○				●	●						A91		
AccuPort 432® 	9.80 - 61.50 (0.3860 - 2.4210)																	●	●	○		●	●		A92		
BT-A Drill 	12.95 - 47.80 (0.5100 - 1.8820)															●	●		●	○	○		●	●	A93		

► Jakákoli řada výrobků s pokračující černou šipkou označuje, že větší nestandardní průměry je možné objednat prostřednictvím poptávky:

● Nejvhodnější ○ Vhodný ○ Použitelný